



704 SW 10th St, Blue Springs, MO 64015
 PO Box 610, Blue Springs, MO 64013 USA
 Tel 816-229-3405 Fax 816-228-9277
 WWW.FIKE.COM



FIKE CORPORATION

破裂試験成績書

販売店データ

販売店:	FIKE JAPAN CORP	(M)	セールスオーダー番号: 573530 4D	2.000
販売店注番:	FJ15-39855/3072		パート番号:	
タグ・図面番号:	RD-6101 X2627004			

製品仕様

型式:	SRL BT	規格:	
口径:	2 IN	Fike Drawing:	
材質:	316 TEF NI	フランジ規格:	JIS 10
設定破裂圧力:	.186 MPAG	バキューム圧力:	
設定破裂温度:	120.00 C	背圧:	

製作データ

製造番号: **1503658** ロット数: **3**

刻印破裂圧力:	MPAG @ *Ambient	Spec:	.195	
	MPAG @ 120.00 C	Spec:	.186	
破裂公差:	MPAG @ *Ambient	Min:	.181	Max: .210
	MPAG @ 120.00 C	Min:	.172	Max: .200
破裂圧力結果:	MPAG @ *Ambient			
	.199 .200			
破裂圧力結果:				

*Ambient temperature is defined as 59 – 86 f (15 – 30 c). Rupture discs are manufactured at ambient temperature to manufacturing range values derived from Fike Temperature Compensation data unless actual temperature tests are performed

使用材質

コンポーネント	材質	ミルシート
Ring Material	316 SST	7945-0114
Seal Material	Nickel 200	625755
Seal Coating/Liner	Fluoropolymer Liner Under	622482

Mill Test Certification attached. Refer to Material Lot Numbers listed above.

SPECIAL NOTES

Discs are stamped with Specified Burst Pressure.

備考

We certify that these components meet applicable specifications, drawings, and requirements of your purchase order. Evidence of compliance is maintained on file in our records and is available for review upon request.

JAMES R. RUBINO

Authorized Quality Representative
 As Approved by the Director of Quality Assurance

01/29/15

Date: ()